



SECTION A-A

NOTES:

1. FOR CYCLE TRACK PAVEMENT DETAILS REFER TO NTA-TCD-700-001 TO 004.
2. FOR KERB PROFILE DETAILS REFER TO NTA-TCD-1100-001 TO 002.
3. FOR KERB CONSTRUCTION DETAILS REFER TO NTA-TCD-1100-011.
4. FOR FOOTWAY CONSTRUCTION DETAILS REFER TO NTA-TCD-1100-015 TO 016.
5. WHERE SETBACK IS 1m OR GREATER REFER TO NTA-TCD-1100-007.
6. THIS DETAIL IS TO BE READ IN CONJUNCTION WITH TL403 OF THE CDM.
7. DESIRABLE KERB UPSTAND OF 0mm TO 6mm WHERE REQUIRED FOR DRAINAGE PURPOSES.
8. TACTILE ARRANGEMENT TO BE AGREED WITH THE APPROVING AUTHORITY.
9. CONSIDERATION IS TO BE GIVEN TO LOCATE TACTILE PAVING OUTSIDE OF THE SWEEPED PATH ANALYSIS AT EACH SIDE ROAD ENTRY.
10. ALL DIMENSIONS IN MILLIMETRES U.N.O.

NOT TO SCALE

 <p>An Roinn Iompair Department of Transport</p>  <p>Údarás Náisiúnta Iompair National Transport Authority</p>	<p>CYCLE DESIGN MANUAL TYPICAL CONSTRUCTION DETAILS</p> <p>Series: NTA-1100: KERBS, FOOTWAYS AND PAVED AREAS</p>	Date	Issue	<p>CONTINUOUS FOOTWAY CROSSING (NO SETBACK)</p>	<p>Drawing File Number NTA-TCD-1100-008</p>
		JAN'26	01		