



NOTES:

1. AGGREGATE SHALL BE ADDED TO THE TOP LAYER OF MASTIC ASPHALT PROVIDING A MINIMUM OF 70% SHOULDER TO SHOULDER COVERAGE AS PER CC-PAV-04012.
2. FOR IRONWORKS OF 300mm DIA. OR LESS, MASTIC SURROUND CAN BE REDUCED TO 150mm IN WIDTH SUBJECT TO AGREEMENT WITH THE CONTRACTING AUTHORITY.
3. IRONWORKS IN CYCLE TRACKS ARE TO BE PRE-LIFTED AND NO MASTIC SURROUND IS REQUIRED SUBJECT TO AGREEMENT WITH THE CONTRACTING AUTHORITY.
4. WHERE MASTIC SURROUND IS REQUIRED IN CYCLEWAYS WITH RED SURFACING, A RED MASTIC AND RED AGGREGATE SHALL BE APPLIED.
5. THE USE OF RED COMPOSITE CHAMBER COVERS SHOULD ALSO BE CONSIDERED IN RED CYCLEWAYS SUBJECT TO AGREEMENT WITH THE CONTRACTING AUTHORITY.
6. ALL DIMENSIONS IN MILLIMETRES U.N.O.

NOT TO SCALE



An Roinn Iompair
Department of Transport



TYPICAL CONSTRUCTION DETAILS

Series:

NTA-700: PAVEMENT

Date

JAN'26

Issue

01

Title

IRONWORK MASTIC
SURROUND

Drawing File Number

NTA-TCD-0700-015